

## NR2

BERTJAN POT



NR2 by Bertjan Pot is an elegant and bright bubble of white or black thread. The lattice pattern creates a fine web that shines and glimmers in the light. The fine web is oval-shaped and bears the signature style of Bertjan Pot; designs created from an experiment with different materials. The integrated LED lamp in NR2 subtly diffuses a soft and magical glow around the room. NR2 is available in two different colours and sizes.

---

### *Detailing*




NR2's lattice patterned web of clean lines falls into place in any modern interior and brings an element of calmness in a maximalist's home.

---

### *Colours*



Just Black




White

# NR2 / Large

## Dimensions

Ø75cm | 29.5"



## Product

**WIDTH** 75cm | 29.5"

**HEIGHT** 53cm | 20.9"

**DEPTH** 75cm | 29.5"

**DIAMETER** 75cm | 29.5"

**WEIGHT NETTO** 1.2kg | 2.65lbs

## Packaging

**WIDTH** 78cm | 30.7"

**HEIGHT** 69cm | 27.2"

**CUBAGE** 0.42m<sup>3</sup> | 14.82ft<sup>3</sup>

**LENGTH** 78cm | 30.7"

**WEIGHT** 8kg | 17.64lbs

## Technical CE

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

B

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

120-277V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

26W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black, White

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### CHROM X

0.48

### CHROM Y

0.41

### COLOUR TEMPERATURE

2468 K (max)

### CRI

81

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

1047 lm

**DIMMING & LIGHTING CONTROL**

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

*See last page for more information about the dimming possibilities.*



---

*Technical UL***MATERIAL**

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

**ENERGY LABEL**

B

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**SHAPE**

Oval

**INPUT VOLTAGE**

120V

**FREQUENCY**

60

**MAX POWER CONSUMPTION**

30W

**LAMPHOLDER**

LED (Solid state)

**LIFETIME**

50000 hours

**CABLE COLOUR**

Black, White

**CABLE LENGTH**

400cm | 157.5"

**CANOPY**

Pebble II Black, ABS, Pebble II White, ABS

**CHROM X**

0.48

**CHROM Y**

0.41

**COLOUR TEMPERATURE**

2468 K (max)

**CRI**

81

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

1047 lm

**DIMMING & LIGHTING CONTROL**

Mains and/or 1-10V dimmable (trailing edge / reverse phase)

*See last page for more information about the dimming possibilities.*



# NR2 / Medium

## Dimensions

55cm | 21.7"



40cm | 15.7"

## Product

**WIDTH** 55cm | 21.7"

**HEIGHT** 40cm | 15.7"

**DEPTH** 55cm | 21.7"

**DIAMETER** 55cm | 21.7"

**WEIGHT NETTO** 0.9kg | 1.98lbs

## Packaging

**WIDTH** 57cm | 22.4"

**HEIGHT** 52cm | 20.5"

**CUBAGE** 0.17m<sup>3</sup> | 5.97ft<sup>3</sup>

**LENGTH** 57cm | 22.4"

**WEIGHT** 3.7kg | 8.16lbs

## Technical CE

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

G

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

208-277V

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

12W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black, White

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### COLOUR TEMPERATURE

2596 K (max)

### CRI

82

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

576 lm

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



---

## Technical UL

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

G

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

120V

### FREQUENCY

60

### MAX POWER CONSUMPTION

16W

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black, White

### CABLE LENGTH

400cm | 157.5"

### CANOPY

Pebble II Black, ABS, Pebble II White, ABS

### COLOUR TEMPERATURE

2700 K (max)

### CRI

82

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

450 lm

### DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

*See last page for more information about the dimming possibilities.*



## *Dimming & Lighting Control*

### *Mains and/or 1-10V dimmable (trailing edge / reverse phase)*

Compatible models: Large CE, Large UL

---

### *Mains, Trailing edge, Reverse phase*

Control the mood with ease. This light fixture can be dimmed using an external Electronic Low Voltage dimmer. Simply connect it to an existing outlet—no need to rewire your home. Choose a dimmer designed for LED lights, suitable for 5 watts or lower, and supporting a C-type (capacitive load). This ensures compatibility and smooth operation. As with all delicate lighting, the experience of dimming may occasionally bring a flicker, hum, or soft buzz.

Compatible models: Medium CE, Medium UL

---